


NOTES:
 1) LENGTH OF CUSTOM STINGERS IS DETERMINED BY THE LAST NUMERICAL DIGIT IN THE MODEL CODE

Model	Conn. Size	"A"	"B"	"C"	"D"	"E"	Body Material	Spring Material	Ball Material	Pressure Max (PSIG)	Temp Max. (°F)
QP-.5-3	1/2"	5.5"	3"	.575"	.250"	1.125"	PVC	Hastelloy C	Ceramic	150	140
QP-.5-5	1/2"	7.5"	5"	.575"	.250"	1.125"	PVC	Hastelloy C	Ceramic	150	140
QK-.5-3	1/2"	5.5"	3"	.575"	.250"	1.125"	Kynar	Hastelloy C	Ceramic	150	280
QK-.5-5	1/2"	7.5"	5"	.575"	.250"	1.125"	Kynar	Hastelloy C	Ceramic	150	280
QS-.5-3	1/2"	5.5"	3"	.530"	.350"	1.125"	316 SS	316 SS	Ceramic	3000	500
QS-.5-5	1/2"	7.5"	5"	.530"	.350"	1.125"	316 SS	316 SS	Ceramic	3000	500
QH-.5-3	1/2"	5.5"	3"	.530"	.350"	1.125"	Hastelloy C	Hastelloy C	Ceramic	3000	500
QH-.5-5	1/2"	7.5"	5"	.530"	.350"	1.125"	Hastelloy C	Hastelloy C	Ceramic	3000	500

		Koflo Corporation 309 CARY POINT DR. CARY, IL 60013	
DATE: 5/23/08		REVISD 12/23/08	
CUSTOMER:		REVISD 04/13/10	
		REVISD 10/21/10	
MODEL NO: INJECTION QUILL		DRAWING NUMBER: KD-979	